

## Product datasheet:

# Cable glands Progress® nickel-plated brass

## Short entry thread Pg

### Approval type: Progress MS

- One-piece sealing insert
- overall length insulated
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.



|                        |                    |
|------------------------|--------------------|
| <b>Article number:</b> | <b>1060.29.275</b> |
| EAN:                   | 7611614106403      |
| Packaging quantity:    | 25                 |
| Price group:           | 500                |

### Dimensions / Form

|                  |       |
|------------------|-------|
| Thread:          | Pg 29 |
| Spanner size:    | 38 mm |
| Dimension H:     | 28 mm |
| Thread length L: | 8 mm  |

### Connections / Entries

|                      |                        |
|----------------------|------------------------|
| Min. clamping range: | 23 mm                  |
| Max. clamping range: | 27.5 mm                |
| Clamping range UL:   | 24.5 - 27.5 mm         |
| clamp technology:    | Compression technology |

### Features

|                |        |
|----------------|--------|
| Thread type:   | metric |
| Thread length: | short  |

### Approvals / Certifications

|                                  |                       |
|----------------------------------|-----------------------|
| Protection class:                | IP69                  |
| Protection class with condition: | IP 68 (10 bar) / IP69 |

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -40 °C |
| Maximum operating temperature: | 100 °C |



Assembly instructions



Planning data