

## Product datasheet:

# Cable glands Progress® nickel-plated brass

## Long entry thread Pg

### Approval type: Progress MS

- Two-piece sealing insert
- overall length insulated
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.



|                        |                |
|------------------------|----------------|
| <b>Article number:</b> | <b>1160.13</b> |
| E-No:                  | 121083308      |
| EAN:                   | 7611614106601  |
| Packaging quantity:    | 50             |

### Dimensions / Form

|                  |       |
|------------------|-------|
| Thread:          | Pg 13 |
| Spanner size:    | 24 mm |
| Dimension H:     | 23 mm |
| Thread length L: | 10 mm |

### Connections / Entries

|                                 |                        |
|---------------------------------|------------------------|
| Min. clamping range:            | 11 mm                  |
| Max. clamping range:            | 14.5 mm                |
| Clamping range with inlet min.: | 8 mm                   |
| Clamping range with inlet max.: | 11 mm                  |
| Clamping range UL:              | 10.6 - 11 mm           |
| clamp technology:               | Compression technology |

### Features

|                |      |
|----------------|------|
| Thread type:   | Pg   |
| Thread length: | long |

### Approvals / Certifications

|                                  |                       |
|----------------------------------|-----------------------|
| Protection class:                | IP69                  |
| Protection class with condition: | IP 68 (10 bar) / IP69 |

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -40 °C |
| Maximum operating temperature: | 100 °C |



Assembly instructions



Planning data