


Product datasheet:

AGRO OTO-UP FTTH E3S Connect®, BEP plug-in, 20m (B2ca)

AGRO OTO-UP FTTH E3S Connect®, BEP plug-in

· 4x fibres, 4x LC/APC



Article number:	⇒ 4176009
E-No:	866700233
EAN:	7611614473697
Packaging quantity:	1

Dimensions / Form

Product length:	86 mm
Product width:	86 mm



Safety / Properties

Halogen-free:	Yes
---------------	-----

Features

Fibre class:	Single Mode OS2 (G.657.A2)
Fibre type:	Single Mode Optical Fibre
Cable/line length:	20 m
Number of fibres (max.):	4
Fibre colour coding:	1 = red, 2 = green, 3 = yellow, 4 = blue

Approvals / Certifications

BauPVo:	B2ca according to EN 50575:2014 + A1:2016
Protection class:	IP20

Storage / Installation / Operation

Minimum storage temperature:	-10 °C
Maximum storage temperature:	60 °C
Minimum installation temperature:	-10 °C
Installation temperature max.:	60 °C
Minimum operating temperature:	-20 °C
Maximum operating temperature:	60 °C

Innovative fibre-optic subscriber connection with an installation depth of max. 32mm for precise flush-mounting installation in all common one-gang junction boxes. The robust metal support ring with alignment markings allows convenient mounting with screw fasteners. Perfect fibre deposit management through a rotatable and removable deposit drum on the back. Equipped with 1x LC/APC Quad coupling including shutter and dust protection. Design compatibility with all common switch manufacturers with a standardised TAE cover