

Product datasheet:

E3S Connect® (FO-SC) subscriber connection, flush-mounting, 2xF, LC/APC QD, L=80m, FO-BD

E3S Connect® (FO-SC) subscriber connection, flush-mounting with E3S fibre-optic cable for connection to the building distributor (FO-BD)

· Scope of delivery: FO subscriber connection, LC-APC coupling and pre-assembled E3S Connect® fibre optic cable



Article number:  **4250076**

EAN: 4013456585249

Packaging quantity: 10

Price group: 730

Safety / Properties

Halogen-free: Yes

Features

Network level: 4

Fibre class: Single Mode OS2 (G.657.A2)

Fibre type: Single Mode Optical Fibre

Cable/line length: 80 m

Splice cassette quantity: 1

Number of fibres (max.): 2

Fibre colour coding: 2-fibres: 1=red, 2=green

Approvals / Certifications

BauPVo: B2ca according to EN 50575:2014 + A1:2016

Protection class: IP20

Storage / Installation / Operation

Minimum storage temperature: -10 °C

Maximum storage temperature: 60 °C

Minimum installation temperature: -10 °C

Installation temperature max.: 60 °C

Minimum operating temperature: -20 °C

Maximum operating temperature: 60 °C

Innovative fibre-optic subscriber connection with an installation depth of max. 32 mm for precise flush-mounting installation in all common one-gang junction boxes. The robust metal support ring with alignment markings allows convenient mounting with screw fasteners. Perfect fibre deposit management through a rotatable and removable deposit drum on the back. Equipped with 1x LC/APC Quad coupling including shutter



Assembly instructions

Product datasheet:

and dust protection. Design compatibility with all common switch manufacturers with a standardised TAE cover.

- Design-compatible with all common TAE covers
- Installation in all KAISER one-gang junction boxes
- Overlength management
- with pre-assembled E3S fibre-optic cable in lengths of 10 - 100 m – other lengths available on request
- Available with 2 or 4 fibres
- High-quality fibre-optic cable G.657.A2 and BauPVo B2ca
- Cable retractable, insertable and blowable
- Pre-assembled cable is delivered in a handy unwinding box
- Subscriber connection enclosed