

## Product datasheet:

### E3S Connect® (FO-SC) subscriber connection, flush-mounting, 2xF, LC/APC QD, L=65m, HTP

#### E3S Connect® (FO-SC) subscriber connection, flush-mounting with E3S fibre-optic cable for connection to the house transfer point (HTP)

· Scope of delivery: FO subscriber connection, LC-APC coupling and pre-assembled E3S Connect® fibre optic cable



|                        |                  |
|------------------------|------------------|
| <b>Article number:</b> | <b>⇒ 4250045</b> |
| EAN:                   | 4013456584600    |
| Packaging quantity:    | 10               |
| Price group:           | 730              |

#### Safety / Properties

|               |     |
|---------------|-----|
| Halogen-free: | Yes |
|---------------|-----|

#### Features

|                           |                            |
|---------------------------|----------------------------|
| Network level:            | 4                          |
| Fibre class:              | Single Mode OS2 (G.657.A2) |
| Fibre type:               | Single Mode Optical Fibre  |
| Cable/line length:        | 65 m                       |
| Splice cassette quantity: | 1                          |
| Number of fibres (max.):  | 2                          |
| Fibre colour coding:      | 2-fibres: 1=red, 2=green   |

#### Approvals / Certifications

|                   |                                           |
|-------------------|-------------------------------------------|
| BauPVo:           | B2ca according to EN 50575:2014 + A1:2016 |
| Protection class: | IP20                                      |

#### Storage / Installation / Operation

|                                   |        |
|-----------------------------------|--------|
| Minimum storage temperature:      | -10 °C |
| Maximum storage temperature:      | 60 °C  |
| Minimum installation temperature: | -10 °C |
| Installation temperature max.:    | 60 °C  |
| Minimum operating temperature:    | -20 °C |
| Maximum operating temperature:    | 60 °C  |

Innovative fibre-optic subscriber connection with an installation depth of max. 32 mm for precise flush-mounting installation in all common one-gang junction boxes. The robust metal support ring with alignment markings allows convenient mounting with screw fasteners. Perfect fibre deposit management through a rotatable and removable deposit drum on the back. Equipped with 1x LC/APC Quad coupling including shutter



Assembly instructions

## Product datasheet:

and dust protection. Design compatibility with all common switch manufacturers with a standardised TAE cover.

- Design-compatible with all common TAE covers
- Installation in all KAISER one-gang junction boxes
- Overlength management
- with pre-assembled E3S fibre-optic cable in lengths of 10 - 100 m – other lengths available on request
- Available with 2 or 4 fibres
- High-quality fibre-optic cable G.657.A2 and BauPVo B2ca
- Cable retractable, insertable and blowable
- Pre-assembled cable is delivered in a handy unwinding box
- Subscriber connection enclosed