

Product datasheet:

Fibre management plate (FMP), 96 fibres, HS, 16 outlets, loop

Hybrid FiberManagement Plate

- 16 hybrid entry ports Ø5,5 - 10,0 mm.
- Flexibility in the FTTX concept.
- Flexibility in fiber network management.
- Integrated strain relief per cable / duct.
- Easy entry seal for each individual cable or duct.
- Structured fibre optic management.
- IP68
- Easy to install.
- Window Cut.



Article number: [AT29388](#)

EAN: 8712259542430



Dimensions / Form

Product length:	380 mm
Product width:	220 mm
Product depth:	130 mm

Safety / Properties

Halogen-free:	Yes
---------------	-----

Features

Network level:	3
Splice cassette quantity:	8
Number of fibres (max.):	96
Microtube size (max.):	10 mm

Approvals / Certifications

Protection class:	IP68
-------------------	------

Storage / Installation / Operation

Minimum storage temperature:	-10 °C
Maximum storage temperature:	60 °C
Minimum installation temperature:	-10 °C
Installation temperature max.:	60 °C
Minimum operating temperature:	-20 °C
Maximum operating temperature:	60 °C



Assembly instructions



Technical information

The FiberManagement Plate(FMP) in combination with our Distribution Closure is an underground distributionpoint. This concept has been developed for a maximum of 48 direct buried Fiber to the Home customercables or duct. The FMP has been designed to separate the civil work and the welding of the fibers. The welding will be done at a later time. With this concept the process of civil work and welding will be optimized. This is

Product datasheet:

due to preassembled parts, the compact size and it is easy to install. This makes the FMP a great fit as an underground distributionpoint. The FMP is also available with a window cut.