

Product datasheet:

FlexBox Connect empty housing, fibre optic building distributor

- Configurable with KAISER ConfiX configurator for FlexBox Connect
- Modular and expandable fibre optic building distributor, assembled
- Can be strung together seamlessly without loss of IP or IK
- Various accessories for flexible installation for different applications, e.g. optional wall modules, profile half-cylinder lock or U-shape for seamless extension of the enclosures
- Can also be used as a fibre optic termination point / house transfer point
- Locking via Torx screws, optionally via profile half-cylinder lock
- Including labelling fields



Article number:  **4240020**

EAN: 4013456592124

Dimensions / Form

Product length:	560 mm
Product width:	289 mm
Product depth:	136 mm



Safety / Properties

Halogen-free:	Yes
---------------	-----



Planning data

Features

Network level:	3 / 4
Splice cassette quantity:	1
Number of fibres (max.):	576
Wall module A:	6x M20/M25 Prägung und Loop Prägung
Wall module B:	
Wall module C:	
Wall module D:	
Wall module E:	
Wall module F:	

Approvals / Certifications

Protection class:	IP54
-------------------	------

Storage / Installation / Operation

Minimum storage temperature:	-10 °C
Maximum storage temperature:	60 °C
Minimum installation temperature:	-10 °C
Installation temperature max.:	60 °C
Minimum operating temperature:	-20 °C
Maximum operating temperature:	60 °C

Product datasheet:

· Including labelling fields