

Product datasheet:

FlexBox Connect splice, 576F, 96x 7 mm microduct, mixer, fibre optic building distributor

- Configurable with KAISER ConfiX configurator for FlexBox Connect
- Modular and expandable fibre optic building distributor, assembled
- Can be strung together seamlessly without loss of IP or IK
- Various accessories for flexible installation for different applications, e.g. optional wall modules, profile half-cylinder lock or U-shape for seamless extension of the enclosures
- Can also be used as a fibre optic termination point / house transfer point
- Locking via Torx screws, optionally via profile half-cylinder lock
- Including labelling fields



Article number:  **4240024**

EAN: 4013456592162

Price group: 720

Dimensions / Form

Product length: 560 mm

Product width: 289 mm

Product depth: 136 mm



Assembly instructions

Features

Network level: 3 / 4

Cable collection holder: 4

Splice cassette quantity: 48

Wall module A: 4x M20/M25 Prägung und Loop Prägung

Wall module B:

Wall module C:

Wall module D:

Wall module E:

Wall module F:

Storage / Installation / Operation

Minimum storage temperature: -10 °C

Maximum storage temperature: 60 °C

Minimum installation temperature: -10 °C

Installation temperature max.: 60 °C

Minimum operating temperature: -20 °C

Maximum operating temperature: 60 °C

- Including labelling fields