

Product datasheet:

Cover for splice cassette

Splice trays

- Snap-in attachment on tray.
- No tools required.
- Scope of delivery: 1x cover 2 mm

Protective cover for fibres and splices in the splice cassette. Toolless installation. Laser warning sign on the top.

Dimensions: 150 x 110 x 2 mm

Colour: Grey

Scope of delivery: 1x cover (2 mm)

Height: 2 mm

Halogen-free: Yes

Mounting options: On universal splice cassette

Storage temperature range: -10 °C / +50°C

Installation temperature range: -10 °C / +60°C

Operating temperature range: -20 °C / +60°C



Article number: **AT29003**

EAN: 8712259291901

Packaging quantity: 25

Safety / Properties

Halogen-free: Yes

Storage / Installation / Operation

Minimum storage temperature: -10 °C

Maximum storage temperature: 50 °C

Minimum installation temperature: -10 °C

Installation temperature max.: 60 °C

Minimum operating temperature: -20 °C

Maximum operating temperature: 60 °C

ETIM Product classification:

Splice cassette

With splice holder:

Suitable for number of splice protections:

Suitable for:

Suitable for number of splice holders:

Length: 150 mm

Width: 100 mm

Height: 2 mm

Mounting method: DIN (top hat) rail/combination-rail/C-rail

By carefully monitoring market requirements, Attema has been able to develop an innovative glass fibre management system with splice trays. Its universal character is shown in particular by the simple snap-in attachment on a standard mounting rail,

Product datasheet:

making it applicable for every housing. The capacity has been doubled cleverly, thus fitting 12 ANT splice protectors in a compact splice tray of only 4 mm high.