

Product datasheet:

End stops for splice cassettes bracket

Splice trays

- Snaps in on standard mounting rails TH 35 - 7.5mm
- Fixed on rails by way of screws.
- Including recess for Velcro fastening.
- For Velcro fastening of max. 16 mm wide.
- Scope of delivery: 2x end stops

Mounting on mounting rail (TH 35.0 – 7.5 mm). Fixing is done with screws. Integrated opening for Velcro fastener strips up to 16 mm wide .

Dimensions: Grey

Scope of delivery: 2x end stops

Halogen-free: Yes

Mounting options: Mounting rail 35.0 – 7.5 mm

Storage temperature range: -10 °C / +50 °C

Installation temperature range: -10 °C / +60 °C

Operating temperature range: -20 °C / +60 °C



Article number:  **AT29005**

EAN: 8712259291888

Packaging quantity: 25

Safety / Properties

Halogen-free: Yes

Storage / Installation / Operation

Minimum storage temperature: -10 °C

Maximum storage temperature: 50 °C

Minimum installation temperature: -10 °C

Installation temperature max.: 60 °C

Minimum operating temperature: -20 °C

Maximum operating temperature: 60 °C



Planning data

By carefully monitoring market requirements, Attema has been able to develop an innovative glass fibre management system with splice trays. Its universal character is shown in particular by the simple snap-in attachment on a standard mounting rail, making it applicable for every housing. The capacity has been doubled cleverly, thus fitting 12 ANT splice protectors in a compact splice tray of only 4 mm high.