

Product datasheet:

End stops for splice cassettes bracket

Splice trays

- Snaps in on standard mounting rails TH 35 - 7.5mm
- Fixed on rails by way of screws.
- Including recess for Velcro fastening.
- For Velcro fastening of max. 16 mm wide.
- Scope of delivery: 2x end stops

Mounting on mounting rail (TH 35.0 – 7.5 mm). Fixing is done with screws. Integrated opening for Velcro fastener strips up to 16 mm wide .

Dimensions: Grey

Scope of delivery: 2x end stops

Halogen-free: Yes

Mounting options: Mounting rail 35.0 – 7.5 mm

Storage temperature range: -10 °C / +50 °C

Installation temperature range: -10 °C / +60 °C

Operating temperature range: -20 °C / +60 °C



Planning data

Article number:  **AT29005**

EAN: 8712259291888

Packaging quantity: 25

Safety / Properties

Halogen-free: Yes

Storage / Installation / Operation

Minimum storage temperature: -10 °C

Maximum storage temperature: 50 °C

Minimum installation temperature: -10 °C

Installation temperature max.: 60 °C

Minimum operating temperature: -20 °C

Maximum operating temperature: 60 °C

ETIM Product classification:

Splice cassette

With splice holder:

Suitable for number of splice protections:

Suitable for:

Suitable for number of splice holders:

Length: 50 mm

Width: 50 mm

Height: 50 mm

Mounting method: DIN (top hat) rail/combination-rail/C-rail

Product datasheet:

By carefully monitoring market requirements, Attema has been able to develop an innovative glass fibre management system with splice trays. Its universal character is shown in particular by the simple snap-in attachment on a standard mounting rail, making it applicable for every housing. The capacity has been doubled cleverly, thus fitting 12 ANT splice protectors in a compact splice tray of only 4 mm high.