

Product datasheet:

Splice cassette, CSP, 24 splices, with holder

Splice trays

· Scope of delivery: cassette, holder

Splice cassette holder with a slot for holding 8 mm splice cassettes. 2x splice cassettes pre-mounted on the holder. Mounting is done on a mounting rail. Splice cassettes are snapped into the slot. Storage for ANT crimp splice protection and mini heat-shrink tubing. Slot for up to 12x fibres and splices per splice cassette .

Dimensions: 150 x 110 x 8 mm

Colour: Grey

Scope of delivery: 2x splice cassettes (8 mm) pre-mounted on holder

Number of fibres: 24

Number of splice cassettes: 2

Splice cassette height: 8 mm

Splice protection holder: ANT crimp splice / mini heat-shrink tubing

Loop length: 300 mm (splice cassette)

Bending radius: R = 30 mm (splice cassette)

Halogen-free: Yes

Mounting options: Mounting rail

Storage temperature range: -10 °C / +50 °C

Installation temperature range: -10 °C / +60 °C

Operating temperature range: -20 °C / +60 °C



Planning data

Article number:  **AT29008**

EAN: 8712259312507

Packaging quantity: 25

Dimensions / Form

Product length: 150 mm

Product width: 110 mm

Product depth: 8 mm

Safety / Properties

Halogen-free: Yes

Features

Network level: 3 / 4

Splice cassette quantity: 2

Number of fibres (max.): 24

Storage / Installation / Operation

Minimum storage temperature: -10 °C

Maximum storage temperature: 50 °C

Minimum installation temperature: -10 °C

Installation temperature max.: 60 °C

Minimum operating temperature: -20 °C

Product datasheet:

Maximum operating temperature:

60 °C

By carefully monitoring market requirements, Attema has been able to develop an innovative glass fibre management system with splice trays. Its universal character is shown in particular by the simple snap-in attachment on a standard mounting rail, making it applicable for every housing. The capacity has been doubled cleverly, thus fitting 12 ANT splice protectors in a compact splice tray of only 4 mm high.