

Product datasheet:

Splice cassette, HS, 24 splices, with holder

Splice trays

· Scope of delivery: cassette, holder

Splice cassette holder for 8 mm splice cassettes. 2x splice cassettes pre-mounted on holder. Mounting on mounting rail. Splice cassettes are snapped into the holder. Slot for HS heat-shrink tubing splice protection. Holds up to 12x fibre optics and splices per splice cassette .

Dimensions: 150 x 110 x 8 mm

Colour: Grey

Scope of delivery: 2x splice cassettes (8 mm) pre-mounted on holder

Number of fibres: 24

Number of splice cassettes: 2

Splice cassette height: 8 mm

Splice protection holder: HS heat-shrink tubing

Loop length: 300 mm (splice cassette)

Bending radius: R = 30 mm (splice cassette)

Halogen-free: Yes

Mounting options: Mounting rail

Storage temperature range: -10 °C / +50 °C

Installation temperature range: -10 °C / +60 °C

Operating temperature range: -20 °C / +60 °C



Planning data

Article number:	⇒ AT29012
EAN:	8712259312545
Packaging quantity:	25
Price group:	710

Dimensions / Form

Product length:	150 mm
Product width:	110 mm
Product depth:	8 mm

Safety / Properties

Halogen-free:	Yes
---------------	-----

Features

Network level:	3 / 4
Splice cassette quantity:	2
Number of fibres (max.):	24

Storage / Installation / Operation

Minimum storage temperature:	-10 °C
Maximum storage temperature:	50 °C
Minimum installation temperature:	-10 °C
Installation temperature max.:	60 °C

Product datasheet:

Minimum operating temperature:	-20 °C
Maximum operating temperature:	60 °C

By carefully monitoring market requirements, Attema has been able to develop an innovative glass fibre management system with splice trays. Its universal character is shown in particular by the simple snap-in attachment on a standard mounting rail, making it applicable for every housing. The capacity has been doubled cleverly, thus fitting 12 ANT splice protectors in a compact splice tray of only 4 mm high.