

## Product datasheet:

# Splitter cassette, 8 mm

### Splice trays

- Special, loose, patented splitter tray including soft foam layer and cover for splitter area. Suited for storing different types and sizes of glass fibre splitters.
- The storage tray is fitted on both sides with a soft foam insert, keeping the sensitive splitters in their position under all circumstances.
- The cover for the splitter storage box simply clicks into the tray and can be easily dismantled using a small screwdriver.
- Dimensions of storage box for splitters: 60 x 18 x 4 mm
- To be applied in combination with universal splice trays. The splitter tray fits on the existing tray case. This enables to exchange or add parts in a given situation.
- Scope of delivery: splitter cassette



The splitter cassette is snapped into the slot of the splice cassette holder. Suitable for holding passive splitters (1:2 – 1:32). The storage space for splitters is 60 x 18 x 4 mm and is secured by a cover. Open with a flat-head screwdriver. Lateral foam padding to secure the passive splitter .

Dimensions: 150 x 110 x 8 mm

Dimensions of splitter storage space: 60 x 18 x 4 mm

Colour: Grey

Scope of delivery: Splitter cassette

Splitter cassette height: 8 mm

Loop length: 300 mm (splice cassette)

Bending radius: R = 30 mm (splice cassette)

Halogen-free: Yes

Mounting options: Mounting rail

Storage temperature range: -10 °C / +50 °C

Installation temperature range: -10 °C / +60 °C

Operating temperature range: -20 °C / +60 °C



Planning data

**Article number:** ➡ AT29009

**EAN:** 8712259312521

**Packaging quantity:** 32

### Dimensions / Form

Product length: 150 mm

Product width: 110 mm

Product depth: 8 mm

### Safety / Properties

Halogen-free: Yes

### Features

Splice cassette quantity: 1

### Storage / Installation / Operation

Minimum storage temperature: -10 °C

Maximum storage temperature: 50 °C

Minimum installation temperature: -10 °C

Installation temperature max.: 60 °C

## Product datasheet:

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -20 °C |
| Maximum operating temperature: | 60 °C  |

### ETIM Product classification: Splice cassette

|                                            |                                            |
|--------------------------------------------|--------------------------------------------|
| With splice holder:                        | No                                         |
| Suitable for number of splice protections: | 0                                          |
| Suitable for:                              | Crimp splice protection                    |
| Suitable for number of splice holders:     | 0                                          |
| Length:                                    | 150 mm                                     |
| Width:                                     | 100 mm                                     |
| Height:                                    | 8 mm                                       |
| Mounting method:                           | DIN (top hat) rail/combination-rail/C-rail |

By carefully monitoring market requirements, Attema has been able to develop an innovative glass fibre management system with splice trays. Its universal character is shown in particular by the simple snap-in attachment on a standard mounting rail, making it applicable for every housing. The capacity has been doubled cleverly, thus fitting 12 ANT splice protectors in a compact splice tray of only 4 mm high.