

Product datasheet:

House transfer point HTP, 2 fibres, 1 LC/APC DX, shutter

- Easy installation.
- Clear assembly sequence.
- Universally applicable (for indoor use).
- Sealable.
- Suitable for most adapters (including 1x LC Duplex adapter with internal shutter).
- Suitable for 8 splice protectors ANT and Mini heatshrink.
- Scope of delivery: HTP with cover, LC/APC duplex coupling



House connection point (HÜP) as termination point for line technology (APL). Suitable for surface mounting. Consisting of base plate, splice cassette, housing cover and coupling bracket. Has a slot for microducts, single-pull seals and fibre optic customer cables. 1x input for microducts and 6x inputs for fibre optic customer cables. Equipped with 1x LC/APC duplex couplings, integrated shutter and dust caps. Coupling locking spring snaps in on the inside. Coupling can only be released by completely opening the housing cover. Cover cap to protect the plug connector. Slot for ANT crimp splice protection and mini heat-shrink tubing. Slot for up to 2x fibre optics and splices distributed across 1x splice cassette. Screw attachment between housing cover and base plate. Approved for funding projects by atene KOM .



Dimensions: 153 x 91 x 61 mm (LxWxH)

Weight: 200 g

Colour: White

Scope of delivery: House transfer point, coupling

Installation type: Surface-mounted

Protection class: IP20

Number of fibres: 2

Number of splice cassettes: 1

Number of couplings: 1

Coupling design: LC/APC DX shutter

atene KOM approved: Yes

Halogen-free: Yes

Loop length: 250 mm (splice cassette)

Bending radius: 30 mm (splice cassette)

Splice protection holder: ANT crimp / mini heat-shrink tubing

Number of cable/conduit entries: 6

Cable/conduit entry Ø: 1x 10.0 mm, 1x 4.5 mm, 4x 4.0 mm

Storage temperature range -10 °C / +60 °C

Installation temperature range -10 °C / +60 °C

Operating temperature range -20 °C / +60 °C



Assembly instructions

Article number:  **AT29221**

EAN: 8712259372570

Packaging quantity: 4

Dimensions / Form

Product length: 153 mm

Product width: 91 mm

Product depth: 61 mm

Safety / Properties

Halogen-free: Yes

atene KOM approved: Yes

Product datasheet:

Features

Network level:	3
Splice cassette quantity:	1
Number of fibres (max.):	2
Microtube size (max.):	10 mm

Approvals / Certifications

Protection class:	IP20
-------------------	------

Storage / Installation / Operation

Minimum storage temperature:	-10 °C
Maximum storage temperature:	60 °C
Minimum installation temperature:	-10 °C
Installation temperature max.:	60 °C
Minimum operating temperature:	-20 °C
Maximum operating temperature:	60 °C

ETIM Product classification: Distributor for telecommunication

Model:	Distributor enclosure
Mounting method:	Surface mounted
With connecting lugs:	No
Max. number of dual cores:	
Mounting dimension (standardised):	Other
110-compatible:	No
LSA:	No
SID:	
Material:	Plastic
Degree of protection (IP):	IP20
Degree of protection (NEMA):	
Colour:	White
Height:	150 mm
Width:	80 mm
Depth:	38 mm
Number of mountable connection strips:	
DIN-compatible:	
Compatible with Grade2TV according to XP-C 90-483:	
Compatible with Grade3TV according to XP-C 90-483:	