

Product datasheet:

House transfer point HTP, 10 fibres, 5 LC/APC DX, shutter

- Easy installation.
- Clear assembly sequence.
- Universally applicable (for indoor use).
- Suitable for 16 splice protectors ANT and Mini heatshrink.
- Approved by atene KOM.
- Scope of delivery: HTP with cover, LC/APC duplex coupling

House transfer point (HÜP) as the end point of line technology (APL). Suitable for surface mounting. Consisting of base plate, splice cassette, housing cover and coupling bracket. Has slots for microducts, single-pull seals and fibre optic customer cables. 1x input for microducts and 6x inputs for fibre optic customer cables. Equipped with 5x LC/APC duplex couplings, integrated shutter and dust caps. Coupling locking spring snaps in on the inside. Coupling can only be released by completely opening the housing cover. Cover cap to protect the plug connector. Slot for ANT crimp splice protection and mini heat-shrink tubing. Slot for up to 10x fibre optics and splices distributed across 1x splice cassette. Screw attachment for the housing cover and base plate. Approved for funding projects by atene KOM .



Dimensions: 153 x 91 x 61 mm (LxWxH)

Weight: 200 g

Colour: White

Scope of delivery: House transfer point, coupling

Installation type: Surface-mounted

Protection class: IP20

Number of fibres: 10

Number of splice cassettes: 1

Number of couplings: 5

Coupling design: LC/APC DX shutter

atene KOM approved: Yes

Halogen-free: Yes

Loop length: 250 mm (splice cassette)

Bending radius: 30 mm (splice cassette)

Splice protection holder: ANT crimp / mini heat-shrink tubing

Number of cable/conduit inputs: 6

Cable/conduit entry Ø: 1x 10.0 mm, 1x 4.5 mm, 4x 4.0 mm

Storage temperature range -10 °C / +60 °C

Installation temperature range -10 °C / +60 °C

Operating temperature range -20 °C / +60 °C

Article number: **➔ AT29225**

EAN: 8712259389523

Packaging quantity: 4

Price group: 720

Dimensions / Form

Product length: 153 mm

Product width: 91 mm

Product depth: 61 mm

Safety / Properties

Halogen-free: Yes

atene KOM approved: Yes

Product datasheet:

Features

Network level:	3
Splice cassette quantity:	1
Number of fibres (max.):	10
Microtube size (max.):	10 mm

Approvals / Certifications

Protection class:	IP20
-------------------	------

Storage / Installation / Operation

Minimum storage temperature:	-10 °C
Maximum storage temperature:	60 °C
Minimum installation temperature:	-10 °C
Installation temperature max.:	60 °C
Minimum operating temperature:	-20 °C
Maximum operating temperature:	60 °C