


Product datasheet:

House transfer point HTP, 6 fibres, 3 LC/APC DX, ready to splice

- Easy installation.
- Clear assembly sequence.
- Universally applicable (for indoor use).
- Suitable for most adapters (incl. 3x LC Duplex adapter with internal shutter).
- Suitable for 16 splice protectors ANT and Mini heatshrink.
- Approved by atene KOM.
- Scope of delivery: HTP with cover, LC/APC duplex coupling, ready to splice



House connection point (HÜP) as termination point for line technology (APL). Suitable for surface mounting. Consisting of base plate, splice cassette, housing cover and coupling bracket. Suitable for microducts, single-pull seals and fibre optic customer cables. 1x slot for microducts and 6x slots for fibre optic customer cables. Equipped with 3x LC/APC duplex couplings with integrated shutter and dust caps. Coupling locking spring snaps in on the inside. Coupling can only be released by completely opening the housing cover. Cover as access protection for the plug connector. Slot for ANT crimp splice protection and mini heat-shrink tubing. Slot for up to 6x fibre optics and splices distributed across 1x splice cassette. Pre-assembled and ready for splicing with LC/APC SX pigtail. Can be sealed with Torx screw, screw attachment of housing cover and base plate. Approved for subsidy projects by atene KOM .



Dimensions: 153 x 91 x 61 mm (LxWxH)

Weight: 200 g

Colour: White

Scope of delivery: House connection point, coupling

Installation type: Surface-mounted

Protection class: IP20

Number of fibres: 6

Number of splice cassettes: 1

Number of couplings: 3

Coupling type: LC/APC DX shutter

Number of pigtails: 6

Pigtail type: LC/APC SX

atene KOM approved: Yes

Halogen-free: Yes

Loop length: 250 mm (splice cassette)

Bending radius: 30 mm (splice cassette)

Splice protection holder: ANT crimp / mini heat-shrink tubing

Number of cable/conduit entries: 6

Cable/conduit entry Ø: 1x 10.0 mm, 1x 4.5 mm, 4x 4.0 mm

Storage temperature range -10 °C / +60 °C

Installation temperature range -10 °C / +60 °C

Operating temperature range -20 °C / +60 °C

Article number: **➔ AT29241**

EAN: 8712259504063

Packaging quantity: 4

Price group: 720

Dimensions / Form

Product length: 153 mm

Product width: 91 mm

Product depth: 61 mm

Product datasheet:

Safety / Properties

Halogen-free:	Yes
atene KOM approved:	Yes

Features

Network level:	3
Splice cassette quantity:	1
Number of fibres (max.):	6

Approvals / Certifications

Protection class:	IP20
-------------------	------

Storage / Installation / Operation

Minimum storage temperature:	-10 °C
Maximum storage temperature:	60 °C
Minimum installation temperature:	-10 °C
Installation temperature max.:	60 °C
Minimum operating temperature:	-20 °C
Maximum operating temperature:	60 °C