


Productgegevensblad:

House transfer point HTP, 12 fibres, 6 LC/APC DX, ready to splice

- Voorgemonteerde LC-duplexadapters en kleurgecodeerde Pigtails.
- Eenvoudige installatie.
- Duidelijke montagevolgorde.
- Universeel toepasbaar (voor binnengebruik).
- Verzegelbaar.
- Geschikt voor de meeste adapters (incl. 6x LC Duplex adapter met interne sluiters).
- Geschikt voor 16 lasbeschermers ANT en Mini heatshrink.
- Goedgekeurd door Atene KOM.
- Scope of delivery: HTP with cover, LC/APC duplex coupling, ready to splice



House connection point (HÜP) as termination point for line technology (APL). Suitable for surface mounting. Consisting of base plate, splice cassette, housing cover and coupling bracket. Has a slot for microducts, single-pull seals and fibre optic customer cables. 1x input for microducts and 6x inputs for fibre optic customer cables. Equipped with 6x LC/APC duplex couplings with integrated shutter and dust caps. Coupling locking spring snaps in on the inside. Coupling can only be released by completely opening the housing cover. Cover cap to protect the plug connector. Slot for ANT crimp splice protection and mini heat-shrink tubing. Slot for up to 12x fibre optics and splices distributed across 1x splice cassette. Pre-assembled and ready for splicing with LC/APC SX pigtail. Sealable with Torx screw, screw attachment between housing cover and base plate. Approved for subsidy projects by atene KOM .

Dimensions: 153 x 91 x 61 mm (LxWxH)

Weight: 200 g

Colour: White

Scope of delivery: House transfer point, coupling

Installation type: Surface-mounted

Protection class: IP20

Number of fibres: 12

Number of splice cassettes: 1

Number of couplings: 6

Coupling design: LC/APC DX shutter

Number of pigtails: 12

Pigtail design: LC/APC SX

Approved by atene KOM: Yes

Halogen-free: Yes

Loop length: 250 mm (splice cassette)

Bending radius: 30 mm (splice cassette)

Splice protection holder: ANT crimp / mini heat-shrink tubing

Number of cable/conduit entries: 6

Cable/conduit entry Ø: 1x 10.0 mm, 1x 4.5 mm, 4x 4.0 mm

Storage temperature range -10 °C / +60 °C

Installation temperature range -10 °C / +60 °C

Operating temperature range -20 °C / +60 °C

halogeen-
vrij



Montage-instructies



Technische informatie

Artikelnummer: ➡ AT29246

EAN: 8712259505893

Verpakkingshoeveelheid: 4

Afmetingen / Vorm

Productlengte: 153 mm

Productbreedte: 91 mm

Veiligheid / Eigenschappen

Halogeenvrij: Ja

Productgegevensblad:

atene KOM goedgekeurd: Ja

Uitrusting

Netniveau:	3
Spleiškassette Anzahl:	1
Aantal vezels:	12
Afmetingen microbuis:	10 mm

Keuringen / Certificeringen

Beschermingsklasse:	IP20
---------------------	------

Opslag / Installatie / Gebruik

Temperatuur opslag min.:	-10 °C
Temperatuur opslag max.:	60 °C
Temperatuur installatie min.:	-10 °C
Temperatuur installatie max.:	60 °C
Gebruikstemperatuur min.:	-20 °C
Gebruikstemperatuur max.:	60 °C

ETIM Productklasse: Schakelbord glasvezel

Geschikt voor aantal koppel/chassisdelen:	8
Geschikt voor aantal module-inzetstukken:	
Met aantal koppelingen/adapters:	6
Met frontplaat:	Nee
Met behuizing:	Nee
Met pigtails:	Nee
Type vezel:	Overig
Vezelklasse:	
APC-uitvoering:	Nee
Connectortype buiten:	LC-duplex
Connectortype binnen:	LC-duplex
Kleur:	Wit
RAL-nummer:	9.010
Montagewijze:	Wandmontage
Aantal hoogte-eenheden:	
Hoogte:	150 mm
Breedte:	80 mm
Diepte:	38 mm