

Product datasheet:

Facade profile XL (3m) 40x80x40

Wall cable duct

- Easy to install.
- Universal applicable.
- Impact-resistant.
- Ability to drill holes over the entire length of the cable duct.
- Suitable to cover up existing type 4 stainless steel profiles.
- Suitable to cover up existing COAX-cable ducts.
- Paintable with use of primer.
- Easy to saw.
- Increased UV resistance.



Article number: [↗ AT29123](#)

EAN: 8712259596723

Packaging quantity: 8

ETIM Product classification: Mini/maxi trunking

Height: 40 mm

Width: 80 mm

Length: 3.000 mm

Usable cross section: 3.200 mm²

Material: Plastic

Material quality: Polyvinyl chloride (PVC)

Halogen free: No

Anti-bacterial treatment: No

Surface protection: Untreated

Suitable for circuit integrity: No

Colour: Grey

Transparent: No

RAL-number: 7.042

Number of permanent partitions: 0

Number of plug-in partitions: 0

Type of fastening: Other

Cover model: None

With cable fixing clip: No

With protective foil: No

With duct connector: No

Delivery on roll: No

Pre-stamping: No

Degree of protection (IP): IP40

Impact strength: IK07



Assembly instructions



Technical information

Product datasheet:

Working temperature:

-20 - 60 °C

The wall cable duct is used on Multi Dwelling Units. It can be used to cover up new-toinstall fiberglass cables, but also to cover up existing smaller sized cable ducts which have been used over the years for example to cover up COAX-cables. Because of the higher demand in broadband these units are in need for fiberglass, which can be installed by using the existing smaller sized cable ducts. The wall cable duct will provide a neat visual finish by covering up both the fiberglass cables as well as the cable ducts installed in the past.