

Product datasheet:

Mains distributor NVt, 48 fibres, HS, 24 outlets, loop, IP65

Street Cabinet + Hybrid FiberManagement Box

- Street cabinet:
 - 60 - 80 µm polyester powder coating.
 - Integrated foundation
 - Stainless steel
 - Universal ½ Euro-cylinder
 - Weatherproof mounting panel
 - Removable front panel
 - Pre-assembled fixing points for ducts and cables.
- FM Box:
 - 24 hybrid entry ports Ø3.0 - 8.0 mm.
 - Flexibility in the FTTX concept.
 - Flexibility in fiber network management.
 - Integrated strain relief per cable / duct.
 - Easy entry seal for each individual cable or duct.
 - Structured management of cables, fibres and welding protectors.
 - Suitable for direct buried customer cables and ducts
 - Easy to install.
 - Save on working time
 - IP65 Waterproof
 - Impact-resistant.
 - Window Cut.
 - Scope of delivery: Gf-NVt, FMB including splice cassettes, 4x stainless steel bolts, sealing material, moisture absorber



Technical information

Power distribution unit consisting of distribution cabinet and splice distributor housing (FMB – Fibre Management Box). Removable front door provides quick access when needed. Lock with profile half cylinder secures against unauthorised access. Two-part design, 1/3 of the distributor is buried below ground level. Distribution cabinet made of stainless steel with 60–80 µm polyester powder coating. Overlength management of 6,300 mm of cable or conduit systems is carried out in the distribution cabinet via a pre-assembled cable and conduit guidance system. Stainless steel mounting wall for fixing the splice distributor housing (FMB). Network distributor complies with protection class IP65.

Splice distributor housing with cover (FMB) for providing a slot for up to 2x fibre optic main cables with a diameter of 4.5 to 8.3 mm and 2x additional break-out openings for diameters of 20/25 mm. 24x outputs with integrated strain relief and holder for individual pull-through sealing for fibre optic cables and microducts with a diameter of 3.0 to 8.0 mm. Cover plugs for unused outputs, dustproof and waterproof closing. Mounting rail for slots to hold up to 4x splice cassette holders. Splice cassette holders for up to 2x splice cassettes (12x fibre optic cables per splice cassette) with a height of 8 mm. Pre-mounted Velcro fastener tape for securing the splice cassettes. Storage for heat-shrink tubing splice protection. Accommodates up to 48x optical fibres and splices distributed across 4x splice cassettes.

Dimensions: 1170 x 500 x 250 mm (LxWxH)

Colour: Grey (RAL 7035)

Scope of delivery: Network distributor, splice distributor housing with cover including splice cassettes (pre-assembled), 4x screws, mounting bracket

Installation type: Above ground

Degree of protection: IP65

Chemical resistance: Yes

Vibration resistance: Yes

Impact resistance: Yes

Halogen-free: Yes

Total fibre count: 48

Fibre count: 12 (splice cassette)

Number of splice cassettes: 8

Splice cassette height: 8 mm

Cascadable (loop function): No

Product datasheet:

Loop length: 300 mm (splice cassette)
 Bending radius: R = 30 mm (splice cassette)
 Splice protection holder: HS heat-shrink tubing
 Cable/conduit entry quantity: 2
 Cable/conduit entry Ø: 4.5 – 8.3 mm
 Cable/conduit break-out opening quantity: 2
 Cable/conduit break-out opening Ø: 20/25 mm
 Cable/conduit exit quantity: 24
 Cable/conduit exit Ø: 3.0 – 8.0 mm
 Fastening option: Screw attachment
 Storage temperature range: -10 °C / +50 °C
 Installation temperature range: -10 °C / +50 °C
 Operating temperature range: -20 °C / +60 °C

Article number:  **AT29316**

EAN: 8712259375359

Dimensions / Form

Product length:	250 mm
Product width:	500 mm
Product depth:	1170 mm

Connections / Entries

For conduit Ø:	25 mm
----------------	-------

Safety / Properties

Halogen-free:	Yes
Vibration resistance:	Yes
Chemical resistance:	Yes
Vibration/sharpness definition:	Yes

Features

Network level:	3
Splice cassette quantity:	4
Number of fibres (max.):	48

Approvals / Certifications

Protection class:	IP65
-------------------	------

Storage / Installation / Operation

Minimum storage temperature:	-10 °C
Maximum storage temperature:	50 °C
Minimum installation temperature:	-10 °C
Installation temperature max.:	50 °C
Minimum operating temperature:	-20 °C
Maximum operating temperature:	60 °C

Product datasheet:

ETIM Product classification: Distributor for telecommunication

Model:	Freestanding distributor
Mounting method:	
With connecting lugs:	No
Max. number of dual cores:	
Mounting dimension (standardised):	Other
110-compatible:	No
LSA:	No
SID:	
Material:	Steel
Degree of protection (IP):	IP65
Degree of protection (NEMA):	
Colour:	Grey
Height:	1.170 mm
Width:	500 mm
Depth:	250 mm
Number of mountable connection strips:	
DIN-compatible:	
Compatible with Grade2TV according to XP-C 90-483:	
Compatible with Grade3TV according to XP-C 90-483:	

Attema's Fiber Management Box (FM Box) with street cabinet is an above-ground distribution point (DP) that has been specially developed for at most 48 buried so-called Fiber-to-the-Home subscriber connection cables or ducts. For the splice mechanic the working method for sorting, splicing and storing the fiberglass cables is the same as for Attema's well-known underground Fiber Management Plate(FMP). Thanks to the pre-assembled parts, the compact format, the supplied suspension bracket and the ease of assembly, the FM-Box is excellent suitable to use in the Attema street. The FM Box with street cabinet is also available with a Window Cut.