

Product datasheet:

Mains distributor (NVt), 192 fibres, CSP, 16 outlets, loop, IP65

Mains distributor (Gf-NVt)

- Street cabinet:
- 60 - 80 µm polyester powder coating.
- Integrated foundation
- Stainless steel
- Universal ½ Euro-cylinder
- Weatherproof mounting panel
- Removable front panel
- Pre-assembled fixing points for ducts and cables.
- FM Box:
- Flexibility in the FTTX concept.
- Flexibility in fiber network management.
- Integrated strain relief per cable / duct.
- Easy entry seal for each individual cable or duct.
- Structured management of cables, fibres and welding protectors.
- Suitable for direct buried customer cables and ducts
- Easy to install.
- Save on working time
- IP65 Waterproof
- Impact-resistant.
- Window Cut.
- Scope of delivery: Gf-NVt, FMB including splice cassettes, 4x stainless steel bolts, sealing material, moisture absorber



Article number:	⇒ AT29326
EAN:	8712259542690
Price group:	710

Dimensions / Form

Product length:	250 mm
Product width:	500 mm
Product depth:	1170 mm

Safety / Properties

Halogen-free:	Yes
Vibration resistance:	Yes
Chemical resistance:	Yes
Vibration/sharpness definition:	Yes

Features

Network level:	3
Splice cassette quantity:	16
Number of fibres (max.):	192
Microtube size (max.):	10 mm

Product datasheet:

Approvals / Certifications

Protection class:	IP65
-------------------	------

Storage / Installation / Operation

Minimum storage temperature:	-10 °C
Maximum storage temperature:	50 °C
Minimum installation temperature:	-10 °C
Installation temperature max.:	50 °C
Minimum operating temperature:	-20 °C
Maximum operating temperature:	60 °C

The mains distributor by the KAISER GROUP is suitable for installation in streets or at crossroads. The advantage over underground distribution points is quick and easy access. Subsequent splicing, cable or conduit laying can be carried out without great effort. The splice distributor box with cover has the protection class IP65 and is protected against dust and water ingress.