

Product datasheet:

Mains distributor (NVt), 96 fibres, CSP, 16 outlets, loop, IP65

Street Cabinet + Hybrid FiberManagement Box

- Street cabinet:
- 60 - 80 µm polyester powder coating.
- Integrated foundation
- Stainless steel
- Universal ½ Euro-cylinder
- Weatherproof mounting panel
- Removable front panel
- Pre-assembled fixing points for ducts and cables.
- FM Box:
- 16 hybrid entry ports Ø5,5 - 10,0 mm.
- Flexibility in the FTTX concept.
- Flexibility in fiber network management.
- Integrated strain relief per cable / duct.
- Easy entry seal for each individual cable or duct.
- Structured management of cables, fibres and welding protectors.
- Suitable for direct buried customer cables and ducts
- Easy to install.
- Save on working time
- IP65 Waterproof
- Impact-resistant.
- Window Cut.
- Scope of delivery: Gf-NVt, FMB including splice cassettes, 4x stainless steel bolts, sealing material, moisture absorber

Mounting bracket for surface mounting of the repair sleeve (CFD). Impact-resistant against external influences, it offers extended protection for the repair sleeve .

Dimensions: 175 x 90 x 85 mm (LxWxH)

Weight: 80 g

Colour: Black

Scope of delivery: Mounting bracket

Installation type: Surface-mounted

UV resistance: Yes



Assembly instructions



Technical information

Article number:  **AT29327**

EAN: 8712259542713

Dimensions / Form

Product length:	250 mm
Product width:	500 mm
Product depth:	1170 mm

Safety / Properties

Halogen-free:	Yes
Vibration resistance:	Yes
Chemical resistance:	Yes
Vibration/sharpness definition:	Yes

Features

Network level:	3
----------------	---

Product datasheet:

Splice cassette quantity:	8
Number of fibres (max.):	96
Microtube size (max.):	10 mm

Approvals / Certifications

Protection class:	IP65
-------------------	------

Storage / Installation / Operation

Minimum storage temperature:	-10 °C
Maximum storage temperature:	50 °C
Minimum installation temperature:	-10 °C
Installation temperature max.:	50 °C
Minimum operating temperature:	-20 °C
Maximum operating temperature:	60 °C

Attema's Fiber Management Box (FM Box) with street cabinet is an above-ground distribution point (DP) that has been specially developed for at most 48 buried so-called Fiber-to-the-Home subscriber connection cables or ducts. For the splice mechanic the working method for sorting, splicing and storing the fiberglass cables is the same as for Attema's well-known underground Fiber Management Plate(FMP). Thanks to the pre-assembled parts, the compact format, the supplied suspension bracket and the ease of assembly, the FM-Box is excellent suitable to use in the Attema street. The FM Box with street cabinet is also available with a Window Cut.