

Product datasheet:

Assembly bracket, repair sleeve CFD

Coupling-/repair closures

- Easy installation
- Universally applicable
- Impact resistant
- Extra protection CFD
- Permanent or temporary outdoor transfer point
- Scope of delivery: cassette, holder



Article number:  **AT29027**

EAN: 8712259330860

Packaging quantity: 5

Dimensions / Form

Product length: 175 mm

Product width: 90 mm

Product depth: 85 mm



Technical information

Safety / Properties

UV resistant: Yes

Features

Network level: 3

ETIM Product classification:

Accessories/spare parts for optic fibre technology

Type of accessory/spare part: Mounting plate

Accessory: No

Spare part: No

Below-ground Fiber-to-the-Home networks are expanding at a steady rate. The European plans for the future are very ambitious. The more customer connection cables or ducts will be installed, the higher the risk that during the installation or afterwards failures due to excavation works will occur. In such event, it is of vital importance that the splice mechanic is able to repair the problem rapidly and in a compact manner. Next to repairing the closures can also be used for extending and/or connecting customer connection cables or ducts. This above-ground as well below-ground. Due to the universal character of the closures you will keep freedom of choice regarding the FttH concept. The clear sequence of actions enables the splice mechanic to execute his works rapidly and faultlessly using a compact closure. The IP68 waterproofness has been tested according to EN 60529.