

Product datasheet:

Wall module B for patch cable

Product data

Scope of delivery: Wall module for the FlexBox Connect
Can be inserted into any side wall or into the centre of the FlexBox Connect
Divides the FlexBox Connect into two halves
Secured by labyrinth IP54 protection
Screw attachment possible on the rear of the FlexBox Connect
Network level: 3/4
Installation type: Surface mounting in the FlexBox Connect
Pre-marked cut-outs: Embossed 2 x M20 or M25, 48 x patch cables
Protection class: IP54 / IK08
Number of cable/conduit entries: 2 x cut-out 8 x M20 or M25
Number of cable/conduit outputs: 48 x patch cables up to 4 mm
Storage temperature range: -10 °C / + 60°C
Installation temperature range: -10 °C / + 60°C
Operating temperature range: -20 °C / + 60°C
Length: 250 mm
Width: 97 mm
Depth: 26.5 mm
Colour: white



Article number:  4240003

EAN: 4013456592001

Packaging quantity: 5

Price group: 720

Dimensions / Form

Product length: 250 mm

Product width: 97 mm

Product depth: 26.5 mm

Features

Network level: 3 / 4

Approvals / Certifications

Protection class: IP54

Storage / Installation / Operation

Minimum storage temperature: -10 °C

Maximum storage temperature: 60 °C

Minimum installation temperature: -10 °C

Installation temperature max.: 60 °C

Minimum operating temperature: -20 °C

Maximum operating temperature: 60 °C



Assembly instructions



Planning data