

Product datasheet:

HWD50L Hollow-Wall Junction box, Ø 16/19 mm

Flush-mounted boxes Hollow-wall

- Fitted with combination nozzles 16/19 mm.
- In combination with sealing cap HWD50L (art. no. AT1065) suitable for airtight applications.
- Standard suitable for sheet thickness 25 mm.
- In combination with spacer (art. no. AT1058) also suitable for sheet thicknesses 9.5 - 12.5 - 15 and 18 mm.
- With bottom outlet.
- Applicable for 'open' walls.
- Sideways fastening by means of HSB-support possible (art. no. AT1052).



Article number: **AT1064**

EAN: 8712259314471

Packaging quantity: 100

Dimensions / Form

Product Ø: 65 mm

Installation opening (wall/ceiling) Ø: 76 mm

Connections / Entries

Number of entries: 2

For conduit Ø: 19 mm

Assembly / Installation

Assembly type: HW (drywall/lightweight construction)

ETIM Product classification:

Box/housing for built-in mounting in the wall/ceiling

Mounting method: Hollow wall

Shape: Round

Construction type: Device connection box (round/square)

Model: Single

Provided with revolving ring: No

Couplable: No

Equipped with:

Diameter: 76 mm


Length:

Width:

Depth:

Inner depth: 50 mm

Suitable for wall/board thickness:



Product datasheet:

Suitable for number of device inserts:	1
Mounting switching equipment:	Screwing
With screws:	No
Number of non-adjustable device fixing lugs:	
Number of adjustable device fixing lugs:	
Housing feed-through by break-out opening:	No
Housing feed-through by seal membrane:	No
Housing feed-through by nozzle:	No
Housing feed-through by step membrane:	No
Suitable for tube diameter:	16/19 mm
Suitable for cable diameter:	
Pipe locking:	
Pipe locking optional:	No
Inlet from the rear:	No
Number of inlets:	2
Number of included spouts:	0
Material:	Plastic
Halogen free:	No
Surface protection:	Untreated
Colour:	Grey
Degree of protection (IP):	IP20
Degree of protection (NEMA):	
Cover model:	None
Transparent cover:	No
Cover attachment:	
Sealable:	No
Circuit integrity:	None
With screening:	No
Airtight:	No
Max. conductor cross section:	6 mm ²
Number of poles of the clamp:	0
Clamp position fixed:	No
Luminaire hook mounting:	No
Nozzle:	Double nozzle
Special application:	None
With partition panel:	
Compliant with BS 4662:	

Attema has a complete range of flush-mounted boxes for hollow walls. Such as fire and smoke resistant flush-mounted boxes, radiation resistant boxes and various inserts, making the boxes also suitable for applications where high(er) demands are made on the

Product datasheet:

air and sound tightness of the walls. Part of the range are hollow wall flush-mounted boxes that are suitable for mounting with different kind of cables, so that they can be used in pluggable installations in utility and residential construction. A good example of this is the Installation 2.0 concept, in which the installation time is greatly reduced and the chance of errors is reduced to a minimum.