

Product datasheet:

DUO-UHW50-BW Hollow-Wall Double-gang Junction box, fire resistant, Ø 16/19 mm

- Maximum 60 minutes fire resistant in an insulated wall.
- Tested in a non-load-bearing wall construction with 2 x 12,5 mm plasterboard panels on both sides.
- Halogen-free.
- Equipped with separate combi spout.
- Equipped with 2 conical tube inlets with integrated locking for both 16 and 19 mm tube.
- Firm mounting of the box in the wall thanks to the metal screw plates with 3-fold pitch.
- No gap formation between switchgear and wall due to very thin, solid support edge of the metal fasteners.



Article number: **↗ AT1075**

EAN: 8712259322957

Packaging quantity: 25

Dimensions / Form

Installation opening (wall/ceiling) Ø: 76 mm

Connections / Entries

Number of entries: 2

For conduit Ø: 19 mm

Assembly / Installation

Assembly type: HW (drywall/lightweight construction)



Certificates

ETIM Product classification:

Box/housing for built-in mounting in the wall/ceiling

Mounting method: Hollow wall

Shape: Round

Construction type: Device connection box (round/square)

Model: Double

Provided with revolving ring: No

Couplable: No

Equipped with:

Diameter: 76 mm

Length: 144 mm

Width: 76 mm

Depth:

Inner depth: 50 mm

Suitable for wall/board thickness:

Suitable for number of device inserts: 2

Product datasheet:

Mounting switching equipment:	Screwing
With screws:	No
Number of non-adjustable device fixing lugs:	
Number of adjustable device fixing lugs:	
Housing feed-through by break-out opening:	No
Housing feed-through by seal membrane:	No
Housing feed-through by nozzle:	No
Housing feed-through by step membrane:	No
Suitable for tube diameter:	16/19 mm
Suitable for cable diameter:	
Pipe locking:	No
Pipe locking optional:	No
Inlet from the rear:	No
Number of inlets:	2
Number of included spouts:	0
Material:	Plastic
Halogen free:	No
Surface protection:	Untreated
Colour:	Red
Degree of protection (IP):	IP20
Degree of protection (NEMA):	
Cover model:	None
Transparent cover:	No
Cover attachment:	
Sealable:	No
Circuit integrity:	E60
With screening:	No
Airtight:	No
Max. conductor cross section:	6 mm ²
Number of poles of the clamp:	0
Clamp position fixed:	No
Luminaire hook mounting:	No
Nozzle:	Double nozzle
Special application:	Fire protection
With partition panel:	
Compliant with BS 4662:	