

Product datasheet:

UHW50 Hollow-Wall Junction box, Ø 16/19 mm

Flush-mounted boxes Hollow-wall

- Plate 1 - 27.5 mm.
- Plasterboard 9.5 - 27.5 mm.
- Also applicable in concrete blocks with a pipe slot (MBI B2 blocks).
- Equipped with 2 conical tube inlets with integrated locking for both 16 and 19 mm tube.
- Firm mounting of the box in the wall thanks to the metal screw plates with 3-fold pitch.
- No gap formation between switchgear and wall due to very thin, solid support edge of the metal fasteners.
- Distance to pipe inlet: 29 mm



Article number: **AT1081**

EAN: 8712259000275

Packaging quantity: 100

Dimensions / Form

Installation opening (wall/ceiling) Ø: 76 mm

Connections / Entries

Number of entries: 2

For conduit Ø: 19 mm

Assembly / Installation

Assembly type: HW (drywall/lightweight construction)

ETIM Product classification:

Box/housing for built-in mounting in the wall/ceiling

Mounting method: Hollow wall

Shape: Round

Construction type: Device connection box (round/square)

Model: Single

Provided with revolving ring: No

Couplable: No

Equipped with:

Diameter: 76 mm

Length:


Width:

Depth:

Inner depth: 50 mm

Suitable for wall/board thickness:

Suitable for number of device inserts: 1



Product datasheet:

Mounting switching equipment:	Screwing
With screws:	No
Number of non-adjustable device fixing lugs:	
Number of adjustable device fixing lugs:	
Housing feed-through by break-out opening:	No
Housing feed-through by seal membrane:	No
Housing feed-through by nozzle:	No
Housing feed-through by step membrane:	No
Suitable for tube diameter:	16/19 mm
Suitable for cable diameter:	
Pipe locking:	No
Pipe locking optional:	No
Inlet from the rear:	No
Number of inlets:	2
Number of included spouts:	0
Material:	Plastic
Halogen free:	No
Surface protection:	Untreated
Colour:	Grey
Degree of protection (IP):	IP20
Degree of protection (NEMA):	
Cover model:	None
Transparent cover:	No
Cover attachment:	
Sealable:	No
Circuit integrity:	None
With screening:	No
Airtight:	No
Max. conductor cross section:	6 mm ²
Number of poles of the clamp:	0
Clamp position fixed:	No
Luminaire hook mounting:	No
Nozzle:	Double nozzle
Special application:	None
With partition panel:	
Compliant with BS 4662:	

Attema has a complete range of flush-mounted boxes for hollow walls. Such as fire and smoke resistant flush-mounted boxes, radiation resistant boxes and various inserts, making the boxes also suitable for applications where high(er) demands are made on the air and sound tightness of the walls. Part of the range are hollow wall flush-mounted boxes that are suitable for mounting with different kind of cables, so that they can be

Product datasheet:

used in pluggable installations in utility and residential construction. A good example of this is the Installation 2.0 concept, in which the installation time is greatly reduced and the chance of errors is reduced to a minimum.