


Product datasheet:

UHW50-BW / RD Hollow-Wall Juntion box, fire-resistant smoke-tight, Ø 16/19 mm

- Smokeproof :Sa and S200.
- Soundproofed.
- Maximum 90 minutes fire resistant in an insulated wall.
- Maximum 60 minutes fire resistant in a non-insulated wall.
- Tested in a non-load-bearing wall construction with 2 x 12,5 mm plasterboard panels on both sides.
- Halogen-free.
- Equipped with 2 conical tube inlets with integrated locking for both 16 and 19 mm tube.
- Firm mounting of the box in the wall thanks to the metal screw plates with 3-fold pitch.
- No gap formation between switchgear and wall due to very thin, solid support edge of the metal fasteners.
- Distance to pipe inlet: 29 mm



Article number:	⇒ AT1115
EAN:	8712259354583
Packaging quantity:	25

Dimensions / Form

Installation opening (wall/ceiling) Ø:	76 mm
--	-------

Connections / Entries

Number of entries:	2
For conduit Ø:	19 mm

Assembly / Installation

Assembly type:	HW (drywall/lightweight construction)
----------------	---------------------------------------

ETIM Product classification:

Box/housing for built-in mounting in the wall/ceiling

Mounting method:	Hollow wall
Shape:	Round
Construction type:	Device connection box (round/square)
Model:	Single
Provided with revolving ring:	No
Couplable:	No
Equipped with:	
Diameter:	76 mm
Length:	
Width:	
Depth:	
Inner depth:	44 mm



Assembly instructions



Certificates

Product datasheet:

Suitable for wall/board thickness:

Suitable for number of device inserts: 1

Mounting switching equipment: Screwing

With screws: No

Number of non-adjustable device fixing lugs:

Number of adjustable device fixing lugs:

Housing feed-through by break-out opening: No

Housing feed-through by seal membrane: No

Housing feed-through by nozzle: No

Housing feed-through by step membrane: No

Suitable for tube diameter: 16/19 mm

Suitable for cable diameter:

Pipe locking: No

Pipe locking optional: No

Inlet from the rear: No

Number of inlets: 2

Number of included spouts: 0

Material: Plastic

Halogen free: No

Surface protection: Untreated

Colour: Red

Degree of protection (IP): IP20

Degree of protection (NEMA):

Cover model: None

Transparent cover: No

Cover attachment:

Sealable: No

Circuit integrity: E60

With screening: No

Airtight: No

Max. conductor cross section: 6 mm²

Number of poles of the clamp: 0

Clamp position fixed: No

Luminaire hook mounting: No

Nozzle: Double nozzle

Special application: Fire protection

With partition panel:

Compliant with BS 4662: