

Product datasheet:

Quickbox® 1x1

SOUND INSULATION BOX

- Compatible with Feller SNAPFIX®
- One-gang boxes for sound insulation walls in buildings
- Maintains the wall's sound insulation protection
- also for opposing installation
- for plate thickness > 10 - 40 mm
- For device screws Ø 3 mm
- Max. tightening torque 0.5 Nm
- does not match with the following types:
- Prestige model by Feller Edizio Due

Quickbox sound insulation box / 1x1
 Inlet box for walls with increased sound insulation requirements
 for device inserts Swiss standard
 DIN EN 60670-1 and DIN 49073, made of plastic with sound insulation sheathing
 Cut hole 83 mm
 Installation depth 50 mm, in cavity wall.
 Combination 1x1
 For panel thicknesses 7-40 mm
 For max. 4 wire entries up to 11.5 mm diameter



Certificates



Planning data

Article number:	9798-77
E-No:	372630019
EAN:	4013456536432
Inner packing / Packaging quantity:	10 / 100

Dimensions / Form

Product Ø:	83 mm
Product length:	83 mm
Product width:	83 mm
Product depth:	50 mm
Installation opening (wall/ceiling) Ø:	83 mm
Drill/cut hole Ø:	83 mm

Assembly / Installation

Assembly type:	HW (drywall/lightweight construction)
----------------	---------------------------------------

Safety / Properties

Special application:	sound insulation
----------------------	------------------

Sound insulation box for use in walls with increased demands on sound protection. The solid box body with additional sound insulation sheathing absorbs and reflects sound, which prevents disturbances in adjacent rooms. Sound insulation is the same as if no installation boxes were installed.

- Compatible with Feller SNAPFIX®