

Product datasheet:

AGRO flush-mounted box 3x3

AGRO flush-mounted box with glow wire test 850°C

- Compatible with Feller SNAPFIX®
- New with strap attachment
- Increased installation volumes
- Simple alignment
- Separator wall for electrical circuit separation
- For device screws Ø 3 mm
- Max. tightening torque 0.5 Nm



Article number: [9902.29.850](#)

E-No: 372633339

EAN: 7611614330082

Packaging quantity: 8

Dimensions / Form

Product length: 190.5 mm

Product width: 190.5 mm

Product depth: 66 mm

Connections / Entries

Number of entries: 20

For conduit Ø: 25 mm

Assembly / Installation

Assembly type: HW (drywall/lightweight construction)

The new lightweight boxes offer even more space for installation and wiring of actuators, WLAN modules and terminals.

Thanks to the additional lugs, the flush-mounted box can now also be installed in panelling/sheeting without connection to a timber stud. A comprehensive design with webs and stabilization walls increases strength while also facilitating safe separation of circuits.

A marker notch on each side of the box enables it to be easily aligned, both horizontally and vertically.

- Compatible with Feller SNAPFIX®
- Additional lug attachment for panelling/sheeting without timber studs
- Increased stability thanks to comprehensive design concept
- Easy alignment using marker notches on each side
- FX4 lug bolts – the fastest screw fastening for flush-mounted boxes in lightweight construction
- Increased installation volumes for wiring



Certificates



Planning data