

Product datasheet:

Aluminium-butyl sealing sleeve

Aluminium-butyl sealing sleeves

- For cables Ø 4 - 15 mm and conduits Ø 15 - 110 mm
- pressing water up to 0.02 bar
- Self-adhesive.
- 1-piece

Aluminium butyl sealing sleeve for permanent sealing of pipe penetrations through masonry, concrete, wood-based materials and much more.
Self-adhesive air-tight sleeve with anti-kink sleeve to compensate for movements during installation or on-site, for conduits with a diameter of 25-32 mm, air-tight design in accordance with DIN 18015-5, Watertight up to 0.02 bar
Temperature resistant from -20°C to 100°C, UV-resistant, halogen-free in accordance with DIN VDE 0604-2-100



Article number:	9079-49
EAN:	4013456538269
Inner packing / Packaging quantity:	10 / 30
Price group:	180

Dimensions / Form

Product length:	150 mm
Product width:	150 mm
Product depth:	30 mm

Connections / Entries

Type of entry:	electric cable
Number of entries:	1
For conduit Ø:	32 mm
Wire entry Ø min.:	25 mm
Wire entry Ø max.:	32 mm

Assembly / Installation

Assembly type:	HW (drywall/lightweight construction)
----------------	---------------------------------------

Safety / Properties

air tightness:	Yes
----------------	-----

For permanent, secure sealing of installation penetrations through masonry, concrete or wooden materials. The highly-elastic sleeves are fitted with non-tear aluminium butyl adhesive flanges and provide maximum adhesion. Some surfaces must be pre-treated with KAISER primer.

- Permanently moisture-proof - for use indoors and outdoors
- Water-sealing effect with non-pressing water up to 0.02 bar
- Especially suitable for sealing in the cellar socle.
- Large contact area to cables and conduits
- Anti-kink sleeve also permanently seals very kinked cables
- Completely toolless wall installation
- Extremely good adhesion



Assembly instructions



Planning data