

## Product datasheet:

# Air-tight sleeves for conduits

## Air-tight sleeve

- Continuous sealing by means of air-tight layers for penetration of cables
- extremely strong adhesion
- Temperature resistance -30°C to +80°C, in the feed-through area up to +120°C
- UV-resistant, halogen-free

Air-tight sleeve for permanent sealing of pipe penetrations through air-tight layers, Self-adhesive air-tight sleeve with anti-kink sleeve to compensate for movements during installation or on-site, for one conduit Ø 25-32 mm, air-tight design in accordance with DIN 18015-5.

Temperature resistant from -30°C to 80°C, UV resistant, halogen-free in accordance with DIN VDE 0604-2-100



**Article number:**  **9059-49**

E-No: 171535338

EAN: 4013456480353

Inner packing / Packaging quantity: 10 / 30

### Dimensions / Form

Product length: 150 mm

Product width: 150 mm

Product depth: 30 mm

### Connections / Entries

Type of entry: electric cable

Number of entries: 1

For conduit Ø: 32 mm

Wire entry Ø min.: 25 mm

Wire entry Ø max.: 32 mm

### Assembly / Installation

Assembly type: HW (drywall/lightweight construction)

### Safety / Properties

air tightness: Yes

Air-tight sleeve for sealing conduit and cable entries in the interior of air-tight building shells.

- extremely strong adhesion
- For guaranteed air-tight feed-throughs, especially in the attic
- 12 types for different conduit and cable diameters
- Suitable for moisture barrier foils, sarking membranes, OSB boards \*



Assembly instructions



Planning data