Product datasheet:

Air-tight sleeves for conduits

Air-tight sleeve

· Continuous sealing by means of air-tight layers for penetration of cables
· extremely strong adhesion
· Temperature resistance -30°C to +80°C, in the feed-through area up to +120°C
· UV-resistant, halogen-free

Air-tight sleeve for permanent sealing of pipe penetrations through air-tight layers. Self-adhesive air-tight sleeve with anti-kink sleeve to compensate for movements during installation or on-site, for conduits with a diameter of 50-75 mm, air-tight design in accordance with DIN 18015-5.
Temperature resistant from -30°C to 80°C, UV resistant, halogen-free in accordance with DIN VDE 0604-2-100

Article number:	**9059-52**
EAN:	4013456532908
Packaging quantity:	4
Price group:	180

air-tight

Dimensions / Form

Product length:	230 mm
Product width:	230 mm
Product depth:	50 mm

Connections / Entries

Type of entry:	electric cable
Number of entries:	1
For conduit Ø:	50 mm
Wire entry Ø min.:	50 mm
Wire entry Ø max.:	75 mm

Assembly / Installation

Assembly type:	HW (drywall/lightweight construction)

Safety / Properties

air tightness:	Yes

Assembly instructions

Planning data

Air-tight sleeve for sealing conduit and cable entries in the interior of air-tight building shells.

· extremely strong adhesion
· For guaranteed air-tight feed-throughs, especially in the attic
· 12 types for different conduit and cable diameters
· Suitable for moisture barrier foils, sarking membranes, OSB boards *