

Product datasheet:

Air-tight sleeves for conduits

Air-tight sleeve

- Continuous sealing by means of air-tight layers for penetration of cables
- extremely strong adhesion
- Temperature resistance -30°C to +80°C, in the feed-through area up to +120°C
- UV-resistant, halogen-free

Air-tight sleeve for permanent sealing of pipe penetrations through air-tight layers. Self-adhesive air-tight sleeve with anti-kink sleeve to compensate for movements during installation or on-site, for conduits with a diameter of 50-75 mm, air-tight design in accordance with DIN 18015-5.

Temperature resistant from -30°C to 80°C, UV resistant, halogen-free in accordance with DIN VDE 0604-2-100



Article number: **9059-52**

E-No: 171535358

EAN: 4013456532908

Packaging quantity: 4

Dimensions / Form

Product length: 230 mm

Product width: 230 mm

Product depth: 50 mm

Connections / Entries

Type of entry: electric cable

Number of entries: 1

For conduit Ø: 50 mm

Wire entry Ø min.: 50 mm

Wire entry Ø max.: 75 mm

Assembly / Installation

Assembly type: HW (drywall/lightweight construction)

Safety / Properties

air tightness: Yes

Air-tight sleeve for sealing conduit and cable entries in the interior of air-tight building shells.

- extremely strong adhesion
- For guaranteed air-tight feed-throughs, especially in the attic
- 12 types for different conduit and cable diameters
- Suitable for moisture barrier foils, sarking membranes, OSB boards *



Assembly instructions



Planning data