

## Product datasheet:

# Air-tight sleeves for conduits

## Air-tight sleeve

- Continuous sealing by means of air-tight layers for penetration of cables
- extremely strong adhesion
- Temperature resistance -30°C to +80°C, in the feed-through area up to +120°C
- UV-resistant, halogen-free

Air-tight sleeve for permanent sealing of pipe penetrations through air-tight layers, Self-adhesive air-tight sleeve with anti-kink sleeve to compensate for movements during installation or on-site, for conduits with a diameter of 100-110 mm, air-tight design in accordance with DIN 18015-5.

Temperature resistant from -30°C to 80°C, UV resistant, halogen-free in accordance with DIN VDE 0604-2-100



**Article number:** **9059-54**

**EAN:** 4013456532922

**Packaging quantity:** 4

**Price group:** 180

### Dimensions / Form

**Product length:** 320 mm

**Product width:** 320 mm

**Product depth:** 50 mm

### Connections / Entries

**Type of entry:** electric cable

**Number of entries:** 1

**Wire entry Ø min.:** 100 mm

**Wire entry Ø max.:** 110 mm

### Assembly / Installation

**Assembly type:** HW (drywall/lightweight construction)

### Safety / Properties

**air tightness:** Yes

Air-tight sleeve for sealing conduit and cable entries in the interior of air-tight building shells.

- extremely strong adhesion
- For guaranteed air-tight feed-throughs, especially in the attic
- 12 types for different conduit and cable diameters
- Suitable for moisture barrier foils, sarking membranes, OSB boards \*



Assembly instructions



Planning data