

Product datasheet:

Fleece-butyl sealing sleeve


Fleece-butyl sealing sleeves

- For cables Ø 4 - 15 mm and conduits Ø 15 - 110 mm
- Fleece-butyl sealing sleeve can be plastered over
- Self-adhesive.
- 1-piece

Fleece butyl sealing sleeve for permanent sealing of pipe penetrations through masonry, concrete, wood-based materials and much more.

Self-adhesive air-tight sleeve with anti-kink sleeve to compensate for movements during installation or on-site, for one conduit Ø 15-22 mm, air-tight design in accordance with DIN 18015-5.

Temperature resistant from -20°C to 100°C, UV resistant, halogen-free in accordance with DIN VDE 0604-2-100



Article number:  **9089-48**

E-No: 171535428

EAN: 4013456538320

Inner packing / Packaging quantity: 10 / 30

Dimensions / Form

Product length: 150 mm

Product width: 150 mm

Product depth: 30 mm

Connections / Entries

Type of entry: electric cable

Number of entries: 1

For conduit Ø: 19 mm

Wire entry Ø min.: 15 mm

Wire entry Ø max.: 22 mm

Assembly / Installation

Assembly type: HW (drywall/lightweight construction)

Safety / Properties

air tightness: Yes



Assembly instructions



Planning data

For permanent, secure sealing of installation penetrations in masonry, concrete or wood materials, etc. The highly-elastic sleeves are fitted with fleece-butyl flanges as plaster bases and provide maximum adhesion. Some surfaces must be pre-treated with KAISER primer.

- Permanently moisture-proof - for use indoors and outdoors
- The fleece sleeve can be plastered over, and is for use in plastered walls and behind composite thermal insulation systems.
- Waterproofing effect with non-pressing water, e.g. against soil moisture