

Product datasheet:

Fleece-butyl sealing sleeve


Fleece-butyl sealing sleeves

- For cables Ø 4 - 15 mm and conduits Ø 15 - 110 mm
- Fleece-butyl sealing sleeve can be plastered over
- Self-adhesive.
- 1-piece

Fleece butyl sealing sleeve for permanent sealing of conduit penetrations through masonry, concrete, wood-based materials and much more.

Self-adhesive air-tight sleeve with anti-kink sleeve to compensate for movements on the installation side or on-site, for conduits with a diameter of 25-32 mm, air-tight design in accordance with DIN 18015-5.

Temperature resistant from -20°C to 100°C, UV resistant, halogen-free in accordance with DIN VDE 0604-2-100



Article number:	9089-49
E-No:	171535438
EAN:	4013456538337
Inner packing / Packaging quantity:	10 / 30

Dimensions / Form

Product length:	150 mm
Product width:	150 mm
Product depth:	30 mm

Connections / Entries

Type of entry:	electric cable
Number of entries:	1
For conduit Ø:	32 mm
Wire entry Ø min.:	25 mm
Wire entry Ø max.:	32 mm

Assembly / Installation

Assembly type:	HW (drywall/lightweight construction)
----------------	---------------------------------------

Safety / Properties

air tightness:	Yes
----------------	-----

For permanent, secure sealing of installation penetrations in masonry, concrete or wood materials, etc. The highly-elastic sleeves are fitted with fleece-butyl flanges as plaster bases and provide maximum adhesion. Some surfaces must be pre-treated with KAISER primer.

- Permanently moisture-proof - for use indoors and outdoors
- The fleece sleeve can be plastered over, and is for use in plastered walls and behind composite thermal insulation systems.
- Waterproofing effect with non-pressing water, e.g. against soil moisture



Assembly instructions



Planning data