

Product datasheet:

O-range ECON® Flex

O-range ECON® Flex

- for accessories and electronic components
- Air-tight design with sealing membranes
- Elastic tunnel
- Combinable with ECON® one-gang junction boxes



Article number:	5027
EAN:	5415160007717
Inner packing / Packaging quantity:	10 / 100
Price group:	121

Dimensions / Form

Product length:	122 mm
Product width:	73 mm
Product depth:	75 mm
Drill/cut hole Ø:	68 mm



Connections / Entries

Number of entries:	6
For conduit Ø:	25 mm

Assembly / Installation

Min. panel thickness:	7 mm
Panel thickness max.:	30 mm
Assembly type:	HW (drywall/lightweight construction)

Safety / Properties

air tightness:	Yes
Halogen-free:	Yes

Air-tight ECON® Flex electronics box with ECON® technology for energy-efficient electrical installation in accordance with EnEV and for installation under clean room or enhanced hygiene conditions. Fast installation is ideal for modernising or extending existing systems. The flexible tunnel makes it easy to install, and creates space for electronic components, cable reserves and terminals.

- Additional sideways terminal compartment for communications and network technology
- Elastic sealing membrane for guaranteed air-tightness
- Toolless cable and conduit entry
- Integrated cable retention
- Can be combined with support connectors, air-tight and fully-insulated