

Product datasheet:

O-range ECON® conduit one-gang junction box, air-tight, Depth 62 mm

Conduit one-gang junction box

- Air-tight design with sealing membranes
- fully-insulated through-wiring for combinations of conduit one-gang junction boxes with support connectors
- toolless conduit entries



Article number: **5029**

EAN: 5415160012506

Inner packing / Packaging quantity: 25 / 250

Price group: 121

Dimensions / Form

Product depth: 62 mm

Drill/cut hole Ø: 68 mm

Connections / Entries

For conduit Ø: 25 mm

Assembly / Installation

Min. panel thickness: 7 mm

Panel thickness max.: 40 mm

Assembly type: HW (drywall/lightweight construction)

Safety / Properties

air tightness: Yes



Planning data

Air-tight one-gang junction box with ECON® technology especially for installation with electrical installation conduit. The box is CEBEC-certified and suitable for energy-efficient electrical installation. 4 entries are optimal for continuous conduit installation e. g. in prefabricated house construction or with data networks. Extremely easy fitting thanks to toolless conduit insertion with opening tab. The sealing membrane guarantees permanent air-tightness and at the same time retention of the conduit.

- Installation in Ø 68 mm cut hole
- Elastic sealing membrane for guaranteed air-tightness
- Toolless conduit entry
- Can be combined with support connectors, air-tight and fully-insulated