

Product datasheet:

One-gang box, Depth 35 mm, halogen-free

Cavity wall installation boxes

- Screws ensure permanent fixing
- 90° conduit entry angle for convenient installation in pipe installations
- Entries can be broken out for cables and conduits
- Integrated cable retention of the NYM cable, self-locking of the conduit
- Fully insulated through-wiring for combinations using support connectors
- Can be combined with all O-range® programme applications

device box, for cavity wall installation.

Cavity wall box, designed as a cavity wall device box in accordance with DIN EN 60670/VDE 0606, made of plastic, halogen-free in accordance with DIN VDE 0604-2-100. Installation opening Ø 60 mm, installation opening Ø 68 mm, depth 35 mm, for panel thickness 7-28 mm, combination distance 71 mm with fully insulated straight couplings, with 2 screw domes and 2 plus-minus device screws, break-out openings for NYM cables (4 x 3 x 1.5 mm²), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Article number:	9061-77
EAN:	4013456219007
Inner packing / Packaging quantity:	25 / 250

Dimensions / Form

Product depth:	35 mm
Drill/cut hole Ø:	68 mm

Assembly / Installation

Min. panel thickness:	7 mm
Panel thickness max.:	28 mm
Assembly type:	HW (drywall/lightweight construction)

Safety / Properties

Halogen-free:	Yes
---------------	-----



Planning data

The KAISER cavity wall installation boxes with proven mounting lug technology and improved product features. A practical design and a large selection of cable and conduit entries allow a large number of applications. Additional boxes for installation in thinly boarded walls or solid wood walls complete the wide range. VDE certification documents the high level of quality.

- Screws ensure permanent fixing
- Entries can be broken out for cables and conduits
- Combinable and through-wiring by using support connectors
- Fixing of devices by means of pre-mounted device screws