

Product datasheet:

One-gang box CEE with sealing ring, Depth 50 mm, halogen-free

Cavity wall installation boxes

- With holding ring
- for device inserts 16 A

Device box, for cavity wall installation.

Cavity wall box, designed as a cavity wall device box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, halogen-free in accordance with DIN VDE 0604-2-100.

Installation opening Ø 70 mm, installation opening Ø 74 mm, depth 48, for panel thickness 12.5-40 mm, with sealing ring Protection class IP 34 according to DIN EN 60529, with 2 screw domes and 2 raised head device screws Ø 4 x 20 mm, break-out openings for NYM cables and data cables as well as for conduits Ø 20 mm (4 x Ø 20 mm, 6 x 3 x 1.5 mm², 1 x 3 x 2.5 mm² or 5 x 1.5 mm², 1 x 5 x 2.5 mm² and 7 x 1.5 mm²), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 850°C, for cavity wall installation, for CEE plugs 16 A



Planning data

Article number: **9075-77**

EAN: 4013456210714

Inner packing / Packaging quantity: 10 / 100

Dimensions / Form

Product depth: 50 mm

Drill/cut hole Ø: 74 mm

Assembly / Installation

Min. panel thickness: 12.5 mm

Panel thickness max.: 40 mm

Assembly type: HW (drywall/lightweight construction)

Safety / Properties

Halogen-free: Yes

Approvals / Certifications

VDE: Yes

The KAISER cavity wall installation boxes with proven mounting lug technology and improved product features. A practical design and a large selection of cable and conduit entries allow a large number of applications. Additional boxes for installation in thinly boarded walls or solid wood walls complete the wide range. VDE certification documents the high level of quality.

- Screws ensure permanent fixing
- Entries can be broken out for cables and conduits
- Combinable and through-wiring by using support connectors
- Fixing of devices by means of pre-mounted device screws