

Product datasheet:

Junction box with universal VDE cover, Depth 50 mm

Cavity wall installation boxes

- with universal VDE cover Art. No. 1184-90
- With holding ring
- with 2 Ø 4 x 16 mm countersunk head screws

Junction box, for cavity wall installation.

Cavity wall box, designed as a cavity wall junction box in accordance with DIN EN 60670/VDE 0606, made of plastic, installation opening Ø 70 mm, installation opening Ø 74 mm, depth 48 mm, for panel thickness 12.5-40 mm, with 2 screw domes and 2 countersunk device screws Ø 4 x 16 mm, with universal VDE cover (Art. no. 1184-90).

Break-out openings for NYM cables and data cables as well as for conduits Ø 20 mm (4 x Ø 20 mm, 6 x 3 x 1.5 mm², 1 x 3 x 2.5 mm² or 5 x 1.5 mm², 1 x 5 x 2.5 mm² or 7 x 1.5 mm²), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Article number: **9071-01**

EAN: 4013456221505

Inner packing / Packaging quantity: 10 / 100

Price group: 120

Dimensions / Form

Product depth: 50 mm

Drill/cut hole Ø: 74 mm

Assembly / Installation

Min. panel thickness: 12.5 mm

Panel thickness max.: 40 mm

Assembly type: HW (drywall/lightweight construction)

Approvals / Certifications

VDE: Yes



Certificates



Planning data

The KAISER cavity wall installation boxes with proven mounting lug technology and improved product features. A practical design and a large selection of cable and conduit entries allow a large number of applications. Additional boxes for installation in thinly boarded walls or solid wood walls complete the wide range. VDE certification documents the high level of quality.

- Screws ensure permanent fixing
- Entries can be broken out for cables and conduits
- Combinable and through-wiring by using support connectors
- Fixing of devices by means of pre-mounted device screws