

Product datasheet:

O-range® one-gang box for thin panelling, depth 35 mm, halogen-free

O-range® one-gang box for thin boardings

- for walls with a small cavity from 35 mm
- for thin boarding
- can be combined with each other

Device box, for cavity wall installation.

Cavity wall box, designed as a cavity wall device box in accordance with DIN EN 60670/VDE 0606, made of plastic, halogen-free in accordance with DIN VDE 0604-2-100.

Installation opening Ø 60 mm, installation opening Ø 68 mm, depth 35 mm, for panel thickness 0.2-30 mm, combination distance 71 mm with fully insulated straight couplings, with 2 screw domes and 2 plus-minus device screws, combination break-out openings for NYM cables and data cables (6 x Ø 4 to 11.5 mm), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Planning data

Article number: **9061-78**

EAN: 4013456550438

Inner packing / Packaging quantity: 25 / 250

Price group: 120

Dimensions / Form

Product depth: 35 mm

Drill/cut hole Ø: 68 mm

Connections / Entries

Number of entries: 6

Assembly / Installation

Min. panel thickness: 0.2 mm

Panel thickness max.: 30 mm

Assembly type: HW (drywall/lightweight construction)

Safety / Properties

Halogen-free: Yes

The one-gang box is available in the O-range® programme for walls with thin boarding or small cavity: thanks to its installation depth of just 35 mm and the zero clamping technology, which ensures a permanently firm hold, it is particularly suitable for walls with little space or thin wall thickness.

- With zero tension technology for thin boarding
- Low installation depth of 35 mm
- Cable entries with integrated cable retention
- Device screws with flat countersunk head
- For cables up to Ø 11.5 mm