

Product datasheet:

Luminaire connection box, Depth 47 mm

Luminaire connection boxes, junction box

- with M5 metal thread for light hooks min. length 55 mm
- maximum load 20 N (2 kg)
- can also be used as ceiling light junction box
- With holding ring
- Important! Always screw in light hook fully.

Ceiling luminaire connection box. For cavity wall installation, cavity wall box, designed as a cavity wall ceiling luminaire connection box, in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic. Installation opening Ø 60 mm, installation opening Ø 68 mm, depth 47 mm, for panel thickness 7-40 mm, with 2 screw domes and 2 plus-minus device screws, break-out openings for NYM cables and for conduits Ø 20 mm (2 x Ø 20 mm, 2 x 3 x 1.5 mm², 2 x 3 x 2.5 mm² or 5 x 1.5 mm²), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Article number:	9063-50
EAN:	4013456241305
Packaging quantity:	10
Price group:	120

Dimensions / Form

Product depth:	47 mm
Drill/cut hole Ø:	68 mm

Connections / Entries

For conduit Ø:	20 mm
----------------	-------

Assembly / Installation

Min. panel thickness:	7 mm
Panel thickness max.:	40 mm
Assembly type:	HW (drywall/lightweight construction)



Certificates



Planning data