

Product datasheet:

Wall light connection box with cover, Depth 40

Luminaire connection boxes, junction box

- with inner fitting cover
- not to be used as a junction box!
- With holding ring

Wall light connection box, for cavity wall installation, cavity wall box, designed as a cavity wall light connection box in accordance with DIN EN 60670/VDE 0606, made of plastic.
Installation opening Ø 2x35 mm, depth 40 mm, for panel thickness 7-30 mm, with internal cover,
break-out openings for NYM cables and for conduits Ø 20 mm (1 x Ø 20 mm, 2 x 3 x 1.5 mm²), protection class IP 30 according to DIN EN 60529, flame retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Article number: **9148-00**

EAN: 4013456241503

Inner packing / Packaging quantity: 25 / 100

Price group: 120

Dimensions / Form

Product depth: 40 mm

Installation opening (wall/ceiling) Ø: 2x35 mm

Drill/cut hole Ø: 2x35 mm

Connections / Entries

For conduit Ø: 20 mm

Assembly / Installation

Min. panel thickness: 7 mm

Panel thickness max.: 30 mm

Assembly type: HW (drywall/lightweight construction)

Approvals / Certifications

VDE: Yes



Certificates



Planning data