

Product datasheet:

Wall light connection box with cover, air tight, Depth 45 mm, halogen-free

Luminaire connection boxes, junction box

- with inner fitting cover
- not to be used as a junction box!
- With holding ring

Wall light connection box, for cavity wall installation, cavity wall box, designed as a cavity wall light connection box, made of plastic, air-tight design in accordance with DIN 18015-5, halogen-free in accordance with DIN VDE 0604-2-100.

Installation opening Ø 35 mm, depth 45 mm, for panel thickness 7-40 mm, with internal cover,

break-out openings for NYM cable (1 x 3 x 1.5 mm²), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Planning data

Article number:  **9248-77**

EAN: 4013456240315

Inner packing / Packaging quantity: 25 / 100

Price group: 121

Dimensions / Form

Product Ø: 35 mm

Product depth: 45 mm

Installation opening (wall/ceiling) Ø: 35 mm

Drill/cut hole Ø: 35 mm

Assembly / Installation

Min. panel thickness: 7 mm

Panel thickness max.: 40 mm

Assembly type: HW (drywall/lightweight construction)

Safety / Properties

air tightness: Yes

Halogen-free: Yes