

Product datasheet:

One-gang box for thin boardings

Air-tight one-gang boxes, one-gang junction boxes, accessories

- for boardings that do not permit any countersinking
- Combinations only possible with boxes with the same Art. No.
- with thin holding ring

Device box, for cavity wall installation.

Cavity wall box for thin boarding, designed as a cavity wall device box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, air-tight design in accordance with DIN 18015-5, installation opening Ø 60 mm, installation opening Ø 68 mm, depth 47 mm, for panel thickness 0.2-40 mm, combination distance 71 mm with fully insulated straight couplings, with 2 screw domes and 2 slotted device screws, 4 markings for wire entries up to Ø 10.5 mm using universal opening cutter (Art. no. 1085-80), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Article number:	9068-01
EAN:	4013456221994
Inner packing / Packaging quantity:	10 / 100
Price group:	121

Dimensions / Form

Product depth:	47 mm
Drill/cut hole Ø:	68 mm

Assembly / Installation

Min. panel thickness:	0.2 mm
Panel thickness max.:	40 mm
Assembly type:	HW (drywall/lightweight construction)

Safety / Properties

air tightness:	Yes
----------------	-----

Approvals / Certifications

VDE:	Yes
------	-----



Certificates



Planning data