

Product datasheet:

One-gang box for thin boardings

Air-tight one-gang boxes, one-gang junction boxes, accessories

- for boardings that do not permit any countersinking
- Combinations only possible with boxes with the same Art. No.
- with thin holding ring

device box, for cavity wall installation.

Cavity wall box for thin boarding, designed as a cavity wall device box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, with air-tight design in accordance with DIN 18015-5, halogen-free in accordance with DIN VDE 0604-2-100. Installation opening Ø 60 mm, installation opening Ø 68 mm, depth 47 mm, for panel thickness 0.2-40 mm, combination distance 71 mm with fully insulated straight couplings, with 2 screw domes and 2 slotted device screws.

4 markings for wire entries up to Ø 10.5 mm using universal opening cutter (Art. no. 1085-80), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Article number: **9068-79**

EAN: 4013456221529

Inner packing / Packaging quantity: 10 / 100

Price group: 121

Dimensions / Form

Product depth: 47 mm

Drill/cut hole Ø: 68 mm

Assembly / Installation

Min. panel thickness: 0.2 mm

Panel thickness max.: 40 mm

Assembly type: HW (drywall/lightweight construction)

Safety / Properties

air tightness: Yes

Halogen-free: Yes

Approvals / Certifications

VDE: Yes



Certificates



Technical information



Planning data