

Product datasheet:

Cavity wall one-gang junction box

Air-tight one-gang boxes, one-gang junction boxes, accessories

- incl. 10 connection pieces (for every 25 boxes)
- With holding ring

One-gang junction box, air-tight, for cavity wall installation.
Cavity wall box, designed as a cavity wall one-gang junction box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, air-tight design in accordance with DIN 18015-5, installation opening Ø 60 mm, installation opening Ø 68 mm, depth 65 mm, for panel thickness 7-40 mm, combination distance 71 mm with fully insulated straight couplings, with 2 plus-minus device screws, 4 markings for electric cable or conduit entries up to max. Ø 25 mm (2 x max. Ø 20 mm, 2 x max. Ø 25 mm) using universal opening cutter (Art. no. 1085-80), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Article number:	9066-01
EAN:	4013456221116
Inner packing / Packaging quantity:	25 / 250
Price group:	121

Dimensions / Form

Product depth:	65 mm
Drill/cut hole Ø:	68 mm

Connections / Entries

For conduit Ø:	25 mm
----------------	-------

Assembly / Installation

Min. panel thickness:	7 mm
Panel thickness max.:	40 mm
Assembly type:	HW (drywall/lightweight construction)

Safety / Properties

air tightness:	Yes
----------------	-----

Approvals / Certifications

VDE:	Yes
------	-----



Certificates



Planning data