

Productgegevensblad:

Hollewand inbouw-verbindingsdoos

Luchtdichte inbouwdozen, verdeeldozen, toebehoren

- met 10 verbindingstukken per verpakkingseenheid 25 stuks
- Met bevestigingsrand

One-gang junction box, air-tight, for cavity wall installation.
Cavity wall box, designed as a cavity wall one-gang junction box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, air-tight design in accordance with DIN 18015-5, installation opening Ø 60 mm, installation opening Ø 68 mm, depth 65 mm, for panel thickness 7-40 mm, combination distance 71 mm with fully insulated straight couplings, with 2 plus-minus device screws, 4 markings for electric cable or conduit entries up to max. Ø 25 mm (2 x max. Ø 20 mm, 2 x max. Ø 25 mm) using universal opening cutter (Art. no. 1085-80), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 850° C, for cavity wall installation



Artikelnummer: **9066-01**

EAN: 4013456221116

Verpakking binnenkant / 25 / 250
Verpakkingshoeveelheid:

Afmetingen / Vorm

Productdiepte: 65 mm

Boorgat-/reesgat-Ø: 68 mm

Aansluitingen / Invoeringen

Voor buis Ø: 25 mm

Montage / Installatie

Plaatdikte min.: 7 mm

Plaatdikte max.: 40 mm

Montagetype: HW (droogbouw/lichtgewicht constructie)

Veiligheid / Eigenschappen

Luchtdichtheid: Ja

Keuringen / Certificeringen

VDE: Ja



Certificaten



Planningsgegevens